

Product Features

- 10X Optical Zoom Indoor/Outdoor 1080P Resolution 4 in 1 AHD PTZ Camera, 5.1-51mm lens
- 4 IN 1 (AHD / TVI / CVI / CVBS) video output
- Max.25/30fps@1080p resolution
- DWDR, Day/Night(ICR), DNR (2D&3D),Auto iris, Auto focus, AWB, AGC,BLC
- OSD menu with humanized design, easy for operation
- Max 200°/s pan & 150°tilt speed; 360° endless rotation
- Up to 128 presets, 4 auto scan, 4 tour, 4 pattern, clock functions
- Built-in 6 pc New Array IR LEDs up to 60m



10X Optical Zoom 1080P 4 in 1 (AHD/TVI/CVI/CVBS) AHD PTZ Camera QH46S

Technical Specifications:

Model	QH46S
Optical zoom	NXT2441H+IMX323 CMOS 2.0MP 5.1-51mm 10x, 0.1Lux/F1.67 Color; / 0.05 Lux/F1.67 B/W H: Appr. 64°(W) ~7.3°(T) / V:Appr. 39.1°(W) ~4.4°(T)
Interface	BNC
Max Imagine Resolution	1920*1080p
Frame	25/30 fps
OSD	Support
Communication	Control over coaxial & RS485
Protocols	Pelco D/P self adaptor
Manual speed	Pan (0.2° ~ 200°/s) ; Tilt (0.2° ~ 150°/s)
Preset speed	200°/S
Rotation	Continuously 360°; tilt 0 ~ 90° with auto-flip
Speed Proportion	Human-oriented focal length/speed adaptation
Preset	128 preset, title can be edited
Auto-flip	Tilt down 90°, with auto-flip 180°
Scan	355° programmable , 4 scan
Pattern	4 patterns, time and speed can be set
Power up Action	Auto restore to previous PTZ and lens status after power failure
Idle Motion	Activate Preset/Pan/Scan/Tour/Pattern if there is no command in the specified period
Time task	Auto activation of Preset/Pan/Scan/Tour/Pattern by preset-time
Decoder	Built-in
Baud rate (RS485)	2400 / 4800 / 9600 / 19200 bps
Temperature	-30 C ~ +60 C
Humidity	0 ~ 95% (Non-condensation)
Protection grade	1500v lightning-proof, surge-proof
Power Supply	DC12V
Net weight	2kg