



























- ▲ Support 16CH 8MP/6MP/5MP/4MP/3MP/1080P/ 960P/ DI/CIF IP input
- ▲ Adopt standard H.265 and H.264 high profile compression format to get high-quality video at much lower bit rate
- ▲ Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- ▲ Multi-mode recording: manual / timer / motion / sensor/smart events
- Playback : 16CH simultaneous playback
- ▲ Search : time slice, time, event, tag, smart search
- ▲ Express and flexible backup via USB, network and so on
- ▲ Pentaplex : preview, record, playback, backup and remote access
- ▲ Remote control via Web or CMS : preview, playback,backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- ▲ Authorization management, log view and device status view
- ▲ 4K output, true high resolution display
- Support NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Andriod OS



















SPECIFICATION

System	
Compression	Standard H.265 / H.264
OS	Embedded Linux

Video	
Network Input	16 CH IPC input
Network Input Resolution	8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/960H/D1/CIF
Output	HDMI×1:3840×2160/1920×1080/1280×1024×768 VGA: 1920 × 1080 / 1280 × 1024/ 1024 × 768

Audio	
Network Input	16 CH IPC audio input
2-way Audio	RCA × 1
Local Output	RCA × 1
Compression	G.711(U/A)

Live View	
Decoding Capability	1CH 8MP;4CH 1080P

Network	
Interface	RJ 45 1000Mbps × 1
Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
Access/Transfer Bandwidth	112/112 (Mbps)

Mobile Device

OS iOS, Andriod

V	1 6

USB	USB 2.0 × 2 (one in the front panel and the other in the rear panel)
Remote Controller	Optional

Record

Record Stream	Dual stream recording
Resolution	8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/960H/D1/CIF
Frame Rate	N:30fps; P:25fps

Playback

Simultaneous Playback	Max. 16 CH
Search	Time slice / time / event / tag search
Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
Function	Play, pause, FF, FB, digital zoom, etc.

Alarm

Mode	Manual, sensor, motion, exception, smart events
Input	Support IPC alarm input
Output	Support IPC alarm output
Triggering	Record, snap, preset, e-mail, etc.

Storage

HDD	SATA3.0 × 1, max 8T

Backup

-	
Local Backup	U disk, USB mobile HDD
Network Backup	Yes

Others	
Power Supply	DC 12V/1.5A
Consumption	≤ 10W (without HDD)
Dimensions (mm)	300 × 248 × 45 (W × D × H)
Work Environment	-10 \sim 50 $^{\circ}\mathrm{C}$, 10% \sim 90% humidity

Dimensions

300mm



248.4mm

