


Product Features



QVP20W

- ▲ 2MP (1920 × 1080) H.265 full real time coding
- ▲ Max. resolution: 1920 × 1080
- ▲ ICR auto switch, true day / night, BLC, HLC, Defog
- ▲ 10m IR night view distance
- ▲ 3D DNR, digital WDR, ROI coding
- ▲ Support Wi-Fi
- ▲ Built-in micro SD card slot
- ▲ 1CH built-in MIC and 1CH built-in speaker
- ▲ 1CH alarm input and 1CH alarm output
- ▲ DC12V/PoE power supply
- ▲ Support smart phone, iPad, remote monitoring
- ▲ Support three streams



Specification

Camera	
Image Sensor	1 / 2.7 "CMOS
Image Size	1920 × 1080
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Iris Type	Fixed Iris
Min. Illumination	0.03 lux@F2.5,AGC ON; 0 lux with IR 0.007 lux@F1.2,AGC ON; 0 lux with IR
Lens	2.8 mm @F1.85, horizontal field of view:116.6 °
Lens Mount	M12
Wide Dynamic Range	Digital WDR
Day&Night Switch	IR Cut Filter
Defog	Yes
BLC	Yes
HLC	Yes
Digital NR	3D DNR
Angle Adjustment	Pan: 0 ~230 ; Tilt: 0°~71°; Rotation: 0°~360°

Image	
Video Compression	1 / 2.7 "CMOS
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile
Resolution	1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, 480 240
Sub Stream	60Hz : D1/CIF (1~30fps); 50HZ: D1/CIF (1~25fps)
Main Stream	60Hz : 1080P(1 ~ 30fps) / 720P(1 ~ 30fps) 50Hz : 1080P(1 ~ 25fps) / 720P(1 ~ 25fps)
Third Stream	60Hz : D1/CIF 480x240 (1~30fps); 50HZ: D1/CIF 480x240 (1~25fps)
Bit Rate	128 Kbps ~ 6Mbps
Bit Rate Type	VBR / CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately

Wi-Fi	
Wireless Standards	IEEE802.11b/g/n
Frequency Range	2.4GHz ~ 2.4835 GHz
Channel Bandwidth	20MHz
Security	WEP, WPA-PSK/WPA2-PSK
Wireless Range	50m
Transfer Rates	11b: 11Mbps 11b: 54Mbps 11n: up to 150Mbps

Interfaces	
Network	RJ45
Video Output	No
Storage	Built-in micro SD card slot; up to 128GB
Alarm	1CH alarm input; 1CH alarm output
Hardware Reset	Yes

Audio

Audio Input	Built-in MIC×1
Audio Output	Built-in Speaker ×1
Audio Compression	G.711A/U
Audio Bit Rate	Self-adaption

Others

Power Supply	DC12V/PoE
Power Consumption	< 4.5W
Dimensions (mm)	130×71.7×71.7
Security	WEP, WPA-PSK/WPA2-PSK
Operating Environment	-10 °C ~ 45°C(-14°F~113°F) Humidity: less than 95 %(non-condensing)
Weight (net)	Approx. 0.14KG
Installation	Ceiling mounting; Wall mounting; Desktop

Functions

Remote Monitoring	Web browsing, CMS remote control
Interface Protocol	ONVIF, GB-T/28181-2011
Storage	Network remote storage; micro SD card storage
PoE	YES
Online Connection	Support simultaneous monitoring for up to 4 users; Support multi-stream real time transmission
Network Protocol	UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1x, UPnP, HTTPs, QoS
Smart Alarm	Motion detection, sensor alarm, PIR alarm, SD card full, SD card error,IP conflict, cable disconnection
General function	Watermark, IP address filtering, video mask, heartbeat, password protection
IR Distance	Up to 10m
PIR	3D DNR Range: 7m

Dimensions

